

CH9-WCA

TENDA CH9-WCA 3MP+3MP DUAL OUTDOOR FULL COLOR PT WiFi CAMERA (N) İkilı obyektivli açıq Wi-Fi pan/əymə kamerası CH9-WCA, 6MP təsvir ölçülü video (3MP+3MP), 360° vizual əhatə dairəsi, tam rəngli gecə görmə, tam duplex birləşdirən yüksək performanslı açıq təhlükəsizlik kamerasıdır. İkitərəfli audio, insan aşkarlanması, avtomobilin aşkarlanması, xəttin kəsişməsinin aşkarlanması, müdaxilənin aşkarlanması, ikili obyektivli ağıllı əlaqə, səs və işıq signalı funksiyaları.



Model	CH9-WCA
Brend	Tenda
Məqəpəpixel	3 MP
Gecə görmə məsafəsi	30m
Səs	İkitərəfli səs
Micro SD	512Gb
Internet	Wifi
İş mühiti	Outdoor

Specification

Image Sensor	1/3 Progressive Scan CMOS sensor
Day and Night	ICR type
Bracket Angle Adjustment	Pan: 0° to 260°
Focal Length	Fixed Lens: 4mm PT Lens: 6mm
Aperture	Fixed Lens: F1.6 PT Lens: F1.6
FOV	Fixed Lens: Horizontal FOV: 82.3°, Vertical FOV: 44.7°, Diagonal FOV: 97.4° PT Lens: Horizontal FOV: 51.8°, Vertical FOV: 28.2°, Diagonal FOV: 60.4°
Supplementary Light	6 IR Lights, 6 Spotlights
Supplementary Light Distance	Up to 30 m/100 ft (depending on environment)
IR Wavelength	850nm
Night Vision Mode	Smart Mode, Full Color Mode, Black & White Mode

Video Encoding Format	Fixed Lens:H.265, H.264 PT Lens:H.265, H.264
Main Stream Resolution	Fixed Lens:2304 × 1296, 1920 × 1080, 1280 × 720 PT Lens:2304 × 1296, 1920 × 1080, 1280 × 720
Sub Stream Resolution	Fixed Lens:640 × 360 PT Lens:640 × 360
Frame Rate	Fixed Lens:1-25fps (2304 × 1296 1-18fps), Default 18fps PT Lens:1-25fps (2304 × 1296 1-18fps), Default 18fps
Bit Rate	Fixed Lens:512kbps -- 4096kbps PT Lens:512kbps -- 4096kbps
Bit Rate Control	Fixed Lens:CBR,VBR PT Lens:CBR,VBR
Audio Encoding Format	G.711A, G.711U, AAC
Audio Sampling Rate	8 kHz
Audio Communication	Two-way Audio, Voice Input
Image Enhancement	DWDR, BLC, HLC, 3D DNR
Privacy Mask	4 Areas
Ethernet Port	1 RJ45, 10Mbps/100Mbps auto-negotiation Ethernet port
ONVIF	Support
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, ARP, WebSockets
Web Browser	Plug-in free live view: Chrome, Edge, Opera
Pan Movement Range	0°--355°
Tilt Movement Range	0°--90°
Preset	6
Patrol	Panoramic Patrol, Preset Patrol
Antenna	Internal antenna
Wireless Standard	IEEE 802.11 b/g/n/ax
Transmission Rate	Up to 287Mbps
Channel Width	20/40 MHz
Modulation	DSSS/OFDM/OFDMA
Frequency Band	2.4GHz: 2412MHz-2472MHz(CH1-CH13)
Transmit Power	2.4GHz: <0.1W(EIRP)
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3-SAE
Smart Detection	Both fixed lens and PT lens are supported motion detection, human detection, vehicle detection, line crossing Detection, intrusion detection
Smart Linkage	Sound&light Alert, Dual-lens Linkage Tracking
DIY Audio	3 Customized Audios
Audio Input	Built-in MIC
Audio Output	Built-in Speaker
Storage	Built-in Micro SD Card Slot, Up to 512 GB
Reset Button	Support
LED Indicator	Dual Color(red & blue) LED Indicator
Power	12V DC,1A,Ø5.5mm&Ø2.1mm Power Plug
Material	Plastic
Product Dimension	203mm x 122mm x 62mm(8.0 × 4.8 × 2.4)
Package Dimension	240mm x 145mm x 193mm(9.4 × 5.7 × 7.6)
Product Weight	527g(1.16lb)
With Package Weight	802g(1.77lb)
Protection Level	IP65
Installation Method	Wall Mounting, Ceiling Mounting, Pole Mounting
Certification	CE, RoHS, FCC, RCM, UKCA
Temperature	Operating Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Storage Temperature: -40°C ~ 70°C (-40°F ~ 158°F)

Humidity	Operating Humidity: 10% ~ 95% RH (non-condensing) Storage Humidity: 3% ~ 95% RH (non-condensing)
Package Contents	Camera Power Adapter (cord length: 3m) Installation Template Mounting Bracket Mounting Accessories Kit Waterproof Kit Quick Installation Guide