

CS700

CUDY CS700 13-IN-1 10Gbps USB-C Dual 4K Docking Station | 150W PSU: 2× HDMI 2.0, 2× DP 1.2a, Dual 4K 1× Upstream PD USB-C (10 Gbps) 2× USB-C 3.2 Gen 2 (10 Gbps, 14W) 4× USB-A 3.2 Gen2 (10 Gbps, 5W) 1× 3.5mm Audio Combo Jack 1× Gigabit Ethernet RJ45 Port 100W Upstream PD (150W Adapter Incl.) DisplayLink DL-6950-N Chipset Aluminum CNC Machining Casing Works with Windows/macOS/Linux/Android



Specification

CS700 1.0	
Chipset	DL-6950-N
CPU Details	DisplayLink
Upstream Connection	1× USB-C 3.2 Gen 2 Port (10 Gbps, Max 100W Charging)
Video Output	• 2× DisplayPort 1.2a • 2× HDMI 2.0
Video Output Resolutions	• 1× 5K (5120×2880) 60 Hz or • 2× 4K (4096×2160) 60 Hz • 5K resolution requires connecting two DisplayPort cables to a compatible 5K monitor
Video Output Modes	Extend, Mirror Android phone supports mirror mode only
USB Ports	• 2× USB-C 3.2 Gen 2 Ports (10 Gbps Max 14W Charging Each) • 4× USB-A 3.2 Gen 2 Ports (10 Gbps Max 5W Charging Each)
Network	1× Gigabit RJ45 Port
Audio and Mic	1× 3.5 mm Combo Jack

Power Input	DC Jack
Physical Buttons	Power On/Off Button
LED	Power
Power Methods	DC
DC	20V 7.5A
Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC Output: 20V 7.5A DC
Max Power Consumption (W)	150W
Idle Power Consumption (W)	2W
Color	Silver Gray Color, Matte Finish
Casing	- Aluminum CNC Machining - Al6061 T5 Base Material - Sandblasting and Anodization
Security	1× Kensington Security Slot
Hardware Requirement	Requires a USB-C 3.2 Gen 2 / USB4 / Thunderbolt 3/4 port on the host device
Compatible OS	- Windows 7 or later - macOS 10.14 or later - Ubuntu LTS 18.04 or later - ChromeOS build RS1 or later - Android 5 or higher (Max 1× 1080P. Ethernet Disabled)
Driver Installation	Auto driver installation for Windows 10/11 and ChromeOS R51+. Manual driver installation is required for macOS, Windows 7/8/8.1, and Ubuntu. DisplayLink Presenter app is required on Android.
Environment	- Operating Temperature: -20~60 °C (-10~140 °F) - Storage Temperature: -40~70 °C (-40~158 °F) - Operating Humidity: 10~90% RH non-condensing - Storage Humidity: 5~90% RH non-condensing
Product Weight	340 g (11.99 oz.)
Dimension	210×85×15.6 mm 8.27×3.35×0.61 inches
- CS700 - Power Adapter - Installation Guide	
Retail Package Weight	EU / US: 1100 g (38.8 oz.)
Retail Package Dimension	226×95.5×98.5 mm 8.9×3.76×3.88 inches
Units per Carton	10
Carton Net Weight	EU / US: 11.1 kg (24.47 lbs)
Carton Gross Weight	EU / US: 11.6 kg (25.57 lbs)
Carton Dimension	49.5×23.8×21.5 cm 19.49×9.37×8.46 inches