

DH-PFM800-4K

DAHUA DH-PFM800-4K 1-CH PASSIVE VIDEO BALUN; Real-time transmission over UTP CAT5E/6 cable; Passive, no need for power supply; Excellent anti-thunder, anti-static and anti-interference capabilities; Compatible format: HDCVI/TVI/AHD/CVBS; With female BNC connector, and pluggable screw terminal connections.



Model	DH-PFM800-4K
Brend	Dahua
Tip	BNC

Specification

Technical Specification				
Model		DH-PFM800-4K		
Properties				
Transmission Signal		1-CH		
Network cable Type		UTP CAT5E/6 (material: CU)		
Transmission Properties	HDCVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M/4K : max.200m (656.17ft)
	TVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)

AHD	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
Video Transmission Properties			
Coaxial Video Connector		BNC-M	
Connection Way		RJ45	
Compatible Format		HDCVI/TVI/AHD/CVBS	
Resolution		720P/1080P/4MP/5MP/4K	
Protection			
ESD	1a contact discharge electricity level 3		
	1b air discharge electricity level 3		
	Per: IEC61000-4-2		
UTP Cable Connector	2KV(different-mode), 4KV(common-mode)		
	Per: IEC61000-4-5		
Impedance			
BNC Male Impedance		75 ohms	
UTP Cable Impedance		100 ohms	
Physical Properties			
Weight		40g (0.09lb) (1 pair)	
Dimension(LxWxH)		173.8mmx19.5mmx21mm (6.84"x0.77"x0.83")	
Shell		ABS	
Color		Black	
Environmental			
Operating Temperature		-30℃~+70℃(-22℉~+158℉)	
Operating Humidity		<95% RH	
Storage Temperature		-40℃~+80℃(-40℉~+176℉)	