

# DS-2CE56D0T-IT3E

DS-2CE56D0T-IT3E

|                       |                  |
|-----------------------|------------------|
| Model                 | DS-2CE56D0T-IT3E |
| Brend                 | Hikvision        |
| Qoruma                | IP67             |
| Növ                   | Analoq           |
| Meqapixel             | 2 MP             |
| İşıqlandırma məsafəsi | 30 m             |
| Obyektiv              | Sabit            |
| Fokus                 | 2.8mm            |
| İşıqlandırma          | İR               |
| Material              | Plastik          |
| İş mühiti             | Indoor           |



## Specification

|                          |                                                                                                                                                           |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Camera                   |                                                                                                                                                           |
| Image Sensor             | 2.0 megapixel progressive scanCMOS                                                                                                                        |
| Max. Resolution          | 1920 (H) × 1080 (V)                                                                                                                                       |
| Min. Illumination        | 0.01 Lux@(F2.0, AGC ON), 0 Lux withIR                                                                                                                     |
| Shutter Time             | PAL: 1/25s to 1/50,000 s;NTSC: 1/30s to 1/50,000 s                                                                                                        |
| Day / Night              | IR Cut Filter                                                                                                                                             |
| Angle Adjustment         | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°                                                                                                       |
| Signal System            | PAL/NTSC                                                                                                                                                  |
| Lens                     |                                                                                                                                                           |
| Lens Type                | 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens                                                                                                              |
| Focal Length / FOV       | 2.8 mm, horizontal FOV:103.55°<br>3.6 mm, horizontal FOV: 82.63° 6 mm,horizontal FOV: 54.38°<br>8 mm, horizontal FOV:37.96<br>12 mm, horizontal FOV:24.36 |
| Lens Mount               | M12                                                                                                                                                       |
| Illuminator              |                                                                                                                                                           |
| Supplement LightRange    | Up to 30 m                                                                                                                                                |
| Image                    |                                                                                                                                                           |
| Image Settings           | Brightness,Mirror,Sharpness,AGC                                                                                                                           |
| Frame Rate               | PAL: 1080P@25fps<br>NTSC: 1080P@30fps                                                                                                                     |
| Day/Night Mode           | Auto/Color/BW (Blackand White)                                                                                                                            |
| Wide Dynamic Range (WDR) | Digital WDR                                                                                                                                               |
| Image Enhancement        | DWDR,BLC                                                                                                                                                  |
| Noise Reduction          | 2D DNR                                                                                                                                                    |

|                           |                                                                         |
|---------------------------|-------------------------------------------------------------------------|
| Supplement Detection(PIR) |                                                                         |
| PIR Range                 | Up to 40 m                                                              |
| Interface                 |                                                                         |
| Video Output              | 1 HD analog output                                                      |
| General                   |                                                                         |
| Power                     | 12 VDC ±30%/PoC.af, max. 4W                                             |
| Material                  | Plastic                                                                 |
| Dimension                 | 110 mm × 93.2 mm (4.33" × 3.67")                                        |
| Weight                    | Approx. 350 g(0.77 lb.)                                                 |
| Operating Condition       | -40 °C to 60 °C(-40 °F to 140 °F), humidity 90% or less(non-condensing) |
| Communication             | HIKVISION-C                                                             |
| Language                  | English                                                                 |
| Approval                  |                                                                         |
| Protection                | IP67                                                                    |