

DS-2CE79H0T-IT3ZE

Hikvision DS-2CE79H0T-IT3ZE 5 mp meqapiksel TVI video kamera; Piksel 2560×1944; IR işıqlandırma - 40 m; F2.7-13.5 mm; Bucaq: 95° - 26°;

Model	DS-2CE79H0T-IT3ZE
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	5 MP
Obyektiv	Motorized
İşıqlandırma məsafəsi	40 m
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
Material	Metal
İş mühiti	Indoor



Specification

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944 (V)
Frame Rate	5 M @ 20 fps, 4 M @ 30 fps, 4M @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Lens	2.7 mm to 13.5 mm motorized varifocal lens
Field of View	horizontal FOV: 95° to 26°, vertical FOV: 72° to 20°, diagonal FOV: 126° to 33°
Lens Mount	Φ14
Day / Night	IR Cut Filter
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Image	
Day/Night Mode	Auto/Color/BW (Black and White)
Image Mode	STD/HIGH-SAT
AGC	Yes
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR, BLC, HLC, Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Smart IR, Sharpness
Interface	
Video Output	1 HD analog output
General	

IR Range	Up to 40 m
Operating Conditions	-40°C to 60°C (-40°Fto140°F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC±15%/PoC.at *You are recommended to use one power adapter for one camera, and use 2-pin powersupply for long-distance power supply.
Consumption	Max 8.4 W
Protection Level	IP67
Material	Metal
Communication	HIKVISION-C
Dimension	123.87 mm × 110.24 mm × 134.3mm (4.87" × 4.34" × 5.29")
Weight	Approx. 595 g(1.31 lb.)