

DS-3E0518P-E/M

DS-3E0518P-E/M Hikvision unmanaged POE+ switch-16 GE + 1 combo SFP ports Long range 300m 230W POE



Model	DS-3E0518P-E/M
Brend	Hikvision
Port sayı	16 Port
PoE	PoE
PoE gücü	120 W
Port sürati	1000mb/s

Specification

Model	DS-3E0518P-E/M
Shell	Metal material
Net Weight	2.50 kg (5.51 lb)
Gross Weight	3.57 kg (7.87 lb)
Dimensions (W × H × D)	440 mm × 44 mm× 220.8 mm (17.3" × 1.7" ×8.7")
Operating Temperature	0 °C to 45 °C (32 °F to 113 °F)
Storage Temperature	-40 °C to 85 °C (-40 °F to 185 °F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	100-240 V AC,50/60 Hz, Max. 2.5A;
Max. Power Consumption	150 W
Power Consumption in Idle	25 W
Installation Mode	Rack (equipped withmounting ears)
Surge Protection	6 kV
Ports	16 × Gigabit PoE port,2× Gigabit fiberoptical port
MAC Address Table	8 K
Switching Capacity	36 Gbps
Packet Forwarding Rate	26.79 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af;IEEE 802.3at;

PoE Power Pin	End-span: 1/2(+), 3/6(-)
PoE Port	PoE: Ports 1 to 16
Max. Port Power	30 W
PoE Power Budget	125 W
EMC	FCC (47 CFR Part15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019,EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue7:2020),RCM (AS/NZS CISPR32: 2015)
Safety	UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD(EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); Reach (Regulation (EC) No.19072006)