

DS-7208HQHI-K1

DS-7208HQHI-K1 HD TVI DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7208HQHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	8 kanal
Meqapixel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	10 TB

Specification

Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding resolution	When 1080p lite mode is not enabled: ,4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF,When 1080p Lite mode is enabled: ,4 MP lite/3 MP/1080p lite/720p lite/VGA/WD1/4CIF/CIF,
Video bit rate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
IP video input	4-ch (up to 12-ch) Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog video input	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
Synchronous playback	8-ch
HDTV input	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25,*: The 3 MP signal input is only available for channel 1 of DS-7204HQHI-K1, for channel 1/2 of DS-7208HQHI-K1, and for channel 1/2/3/4 of DS-7216HQHI-K1.,
VGA/HDMI output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Remote connections	64
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
SATA	1 SATA interface
Capacity	Up to 10 TB capacity for each disk
Alarm in/out	N/A

USB interface	2 × USB 2.0
Serial interface	RS-485 (half-duplex)
Power supply	12 VDC
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
Weights (without HDD)	≤ 1.78 kg (3.9 lb)
Consumption (without HDD)	≤ 7.5 W