

DS-7616NI-K2

DS-7616NI-K2 NETWORK DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7616NI-K2
Brend	Hikvision
Növ	NVR
Kanal sayı	16 kanal
Meqapixel	12 MP
Max HDD sayı	2 HDD
Max HDD həcmi	10 TB

Specification

Video and Audio	
IP Video Input	16-ch
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	160 Mbps
HDMI Output	4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920× 1080/60 Hz,1600 × 1200/60 Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
VGA Output	1920 × 1080/60Hz, 1280 × 1024/60 Hz,1280 × 720/60Hz
Video Output Mode	HDMI/VGA independent output
Audio Input	1-ch, RCA (2.0Vp-p, 1 KΩ)
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p,1kΩ, using the audio input)
Decoding	
Decoding Format	H.265/H.265+/H.264/H.264+
Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/ 1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-ch
Decoding Capability	1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p (30 fps)
Stream Type	Video, Video& Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726
Network	
Remote Connection	128-ch

Network Protocol	TCP/IP, DHCP, IPv4,IPv6, DNS, DDNS,NTP, RTSP, SADP,SMTP, SNMP, NFS,iSCSI, ISUP, UPnP™, HTTP,HTTPS
Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each HDD
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 2.0
Alarm In/Out	4/1
General	
Power Supply	12 VDC, 3.33 A
Consumption	≤ 15 W (without HDD)
Working Temperature	-10 °C to 55°C (14 °F to 131°F)
Working Humidity	10 to 90 %
Dimension (W × D × H)	385 × 315× 52 mm (15.2" × 12.4" × 2.0")
Weight	≤ 1 kg (without HDD, 2.2 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017