

DS-8664NI-I8

DS-8664NI-I8 NETWORK DIGITAL VIDEO RECORDER HIKVISION



Model	DS-8664NI-I8
Brend	Hikvision
Növ	NVR
Kanal sayı	64 kanal
Meqapixel	12 MP
Max HDD sayı	8 HDD
Max HDD həcmi	10 TB

Specification

Video and audio

IP video input	64 channels Resolution up to 12 MP 32 MP/24 MP/ 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/ UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: resolution 32 MP and 24 MP are only available for channel 1 when Ultra HD resolution mode is enabled.
Input Bandwidth	320 Mbit/s
Output Bandwidth	256 Mbit/s
Input Bandwidth (RAID Mode)	200 Mb/s
Output Bandwidth (RAID Mode)	200 Mb/s
1 HDMI output	4K (3840×2160)/60Hz, 4K (3840×2160)/30Hz, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 10 24× 768/60 Hz
2 HDMI output	1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
1 VGA output	1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
2 VGA output	1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Video output	1 HDMI and 1 VGA provide simultaneous video output and is used as the main output; 2 HDMI and 2 VGA provide simultaneous video output and can be used as auxiliary output;
CVBS output (optional)	1 channel, BNC (1.0 V pp, 75 Ohm), resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio output	2 channels, RCA (linear, 1 kOhm)
Two-way audio	1 channel, RCA (2.0 V pp, 1 kOhm, when using audio input)

Decoding

Decoding Format	H.265+/H.265/H.264+/H.264/MPEG4
Recording permission	32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF 32 MP/24 MP/12 MP/8 MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF *: 32MP and 24MP resolution is only available for channel 1 when Ultra resolution mode is enabled HD.
Synchronized playback	16 channels
Playback options	1 channel, @ 32 MP (30 fps)/2 channels, @ 12 MP (20 fps)/4 channels, @ 8 MP (25 fps)/8 channels @ 4 MP (30 fps) /16 channels @ 1080p (30 fps)
Dual stream recording	Supported
Stream type	Video, video and audio

Audio compression	G.711ulaw/G.711alaw/G.722/G.726
-------------------	---------------------------------

Net

Remote connections	128
Protocols	TCP/IP, DHCP, HIK Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS

RAID

RAID type	RAID0, RAID1, RAID5, RAID6 and RAID10 (minimum 4 TB for each HDD)
-----------	---

Auxiliary Interfaces

Serial interface	RS-232; RS-485; keyboard
SATA	8 SATA interfaces
eSATA	1 eSATA interface
Capacity	Up to 10 TB each drive
Alarm input/output	16/4
USB	Front panel: 2 × USB 2.0; rear panel: 1 × USB 3.0

Basics

Nutrition	AC 100 to 240 V, 50 to 60 Hz
Power consumption (without HDD)	≤30W
Working temperature	-10 to +55 °C
Operating humidity	From 10 to 90%
Dimensions	445 × 470 × 94 mm
Weight (without storage)	≤ 8 kg

Certificates

FCC	Part 15 Subpart B, ANSI C63.4-2014
C.E.	EN 55032:2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4