

DS-KB8113-IME1

DS-KB8113-IME1 B IP DOMOFON CAGRI PANELI HIKVISION



Model	DS-KB8113-IME1
Brend	Hikvision
Bağlantı tipi	IP
Cihaz	Zəng
PoE	PoE
Material	Plastik

Specification

System parameters	
Operation system	Embedded Linuxoperation system
ROM	32 M
RAM	256 M
Processor	Embedded MCU Processor
Display parameters	
Screen size	/
Operation method	/
Type	/
Resolution	/
Video parameters	
Lens	1
Resolution	Main stream: 1920 × 1080 Sub stream : 640 × 480
FOV	Horizontal:95° Vertical:54°
Wide dynamic range(WDR)	Support
Supplement light	IR supplement
Video compression standard	H.264
Audio parameters	

Audio input	Built-in omnidirectional microphone
Audio compression standard	G.711 U/G.711 A
Audio output	Built-in loudspeaker (More than 80 dBwithin 30 cm)
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
Face capacity	/
Card capacity	/
Linked indoor station capacity	1
Sub door station capacity	16
Network parameters	
Network protocol	TCP/IP, RSTP, SIP
Wi-Fi	/
Bluetooth	/
3G/4G	/
Device interfaces	
Alarm input	1
Network interface	1 RJ-45, 10/100 Mbps self-adaptive
Lock control	1 relay, Max. to 30 VDC, 2 A)
General	
Button	1
Installation	Surface mounting
Weight	Net Weight: 0.795 kg Gross Weight: 0.992 kg
Protective level	IP65, IK09
Working temperature	-30 °C to 50 °C(-22 °F to 122 °F)
Working humidity	10% to 90% (no-condensing)
Dimension (W × H × D)	161.85 mm × 74.13 mm × 53.2 mm(6.37" × 2.92" × 2.09")
Battery	/
Power supply	12 VDC, IEEE802.3af, standard PoE
Application environment	Outdoor and Indoor
Power consumption	≤ 10 W
Language	English,French,Portuguese,Spanish,Russian,German,Italian,Polish,Arabic,Turkish,Vietnamese,Hungarian,Dutch,Romanian,Czech,Bulgarian,Ukrainian,Croatian,Serbian,Greek, Slovakia,BrazilianPortuguese