

DS-KIS303-P

DS-KIS303-P Hybrid Intercom Kit

Model	DS-KIS303-P
Brend	Hikvision
Bağlantı tipi	IP
Cihaz	KİT
WIFI	WIFI
Yaddaş	SD Card
Material	Plastik
PoE	PoE



Specification

Doorstation	
Resolution	1920 x 1080
FOV	Horizontal: 66.2° Vertical: 37.2°
Doorstation	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Doorstation	
I/O output	1 relay output
Four-wire	1 for 4-wire interface
Doorstation	
Power supply	12 VDC
Power consumption	Max. 5 W
Working temperature	-10° C to 55° C (14°F to 131° F)
Working humidity	10% to 90%
Dimensions	135.14 mm x 49.6mm x 41.93 mm (5.32" x 1.95" x 1.65")
Indoorstation	
Operation system	Embedded Linux operation system
RAM	128 MB
ROM	32 MB
Indoorstation	
Size	7-inch colorful TFT screen
Operation method	Capacitive touchscreen

Type	Colorful TFT screen
Resolution	1024 × 600
Indoorstation	
Resolution	/
Lens	/
WDR	/
FOV	/
Indoorstation	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio compression Rate	64 Kps
Audio compression standard	G.711 U G.711 A
Volume adjustment	Adjustable
Audio quality	Noise suppression and echo cancellation
Indoorstation	
Linked IPC capacity	16
Notice capacity	200
Linked indoor extensions capacity	5
Linked doorphone capacity	2 analog doorphones, 15 IP doorphones Max.
Indoorstation	
Wi-Fi	Wi-Fi 802.11b/g/n
3G/4G	/
Bluetooth	/
Protocol	TCP/IP, SIP, RTSP
Indoorstation	
Network interface	1 RJ-45/100 Mbps self-adaptive
RS-485	1
Alarm input	2-ch alarm inputs
Alarm output	2
Power input	1, 12 VDC
TAMPER	/
TF card	Max to 128 G, SD 2.0 or lowerversion
USB interface	/
Four-wire interface	2
Indoorstation	
Button	0
Power supply	IEEE802.3af, Standard PoE, 12V DC
Power consumption	≤ 6 W
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90%
Dimensions (W × H × D)	200 mm × 140 mm × 23.6mm (7.9" × 5.5" × 0.9")
Installation	Surface mounting
Application environment	Indoor
Protective level	/
Weight	With package: 365 g
	Without package: 355 g