

GNT-IG1210FP-AC

GNT-IG1210FP-AC Industrial 8 Port Full Gigabit Unmanaged PoE Switch



Model	GNT-IG1210FP-AC
Brend	Genata
PoE gücü	120 W
Port sayı	8 Port
PoE	PoE
Port sürati	1000mb/s

Specification

Model	GNT-IG1210FP-AC
Ports	PoE (1~6):10/100/1000Mbps PoE ports (RJ45), PoE (7~8):10/100/1000Mbps PoE ports (RJ45), Support bt 60W HighPower SFP(1~2):10/100/1000Mbps SFP ports
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:20Gbps Network Latency (10 to 1000Mbps): ≤16μs (use the 64byte package size) MAC address table: 8K Packet forwarding rate: 14.88Mpps The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port; 1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T / IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at/bt Power over Ethernet

Power Support	Power Input:90~264VAC, DC48-52V input,Triple Redundancy, Totals130W AI Watchdog: Port 1~8 Power Output:PoE1~6 Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Protection Level:IP40, Lightning Protection:6KV, ESD Protection:8KV, IEC61000-4-5 Surge Protection 6KV, IEC61000-4-2 ESD 8/15KV
Physical Specifications	Size(H*D*W): 145*110*88mm, Weight: 0.9KG/Pcs
Package	Size(L*W*H): 400*360*230mm(CTN Box); 12Pcs/CTN
Working Environment	Operating Temperature: -40°C~70°C
	Storage Temperature: -40°C~70°C
	Relative Humidity: 5%~90% Non-condensing
	Heat dissipation mode: fanless design, natural heat dissipation
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device:1 year
Package Content	User Manual,Terminal