

GNT-MP1420ES

GNT-MP1420ES16p 2Up-Link 2SFP 250m AI PoE SwitchGenata



Model	GNT-MP1420ES
Brend	Genata
PoE gücü	250 W
Port sayı	16 Port
PoE	PoE
Port sürati	100mb/s

Specification

Model	GNT-MP1420ES
Ports	PoE (1~14):10/100Mbps PoE ports (RJ45) PoE (15~16):10/100Mbps PoE ports,Support bt 60W High Power LAN (17~18):10/100/1000Mbps uplink ports (RJ45) SFP (19~20):10/100/1000Mbps SFPport
Transmission Rate	2000Mbps FullDuplex; 10 or 100Mbps Half Duplex
Transmission Distance	Port1~15: 10/100Mbps 130meters; 10Mbps Auto-adaption 250meters Port16: 10/100Mbps 130meters
Performance Specification	Bandwidth:11.2Gbps
	Network Latency(1000Mbps): ≤16µs (use the 64bytepackage size)
	MAC address table: 8K
	The FrameFilter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control

IEEE 802.3af/at/bt Power over Ethernet	
Power Support	Power Input:AC 90~240V Totals≤240W AI Watchdog: Port 1~16 Power Output:PoE1~14 Port:1/2(+52V),3/6(GND)≤30W PoE15~16 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 270mm*170mm*45mm, Weight:1.75KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device:1 year
Package Content	AC Power Cable,User Manual