

GNT-P4804F6

GNT-P4804F6 6pMb 2pGb +2SFP AI Waterproof PoE Switch Genata



Model	GNT-P4804F6
Brend	Genata
PoE gücü	120 W
Port sayı	8 Port
PoE	PoE
Port sürati	100mb/s

Specification

Model	GNT-P4804F6
Ports	PoE (1~6):10/100Mbps PoE ports (RJ45) PoE (7~8):10/100/1000Mbps PoEports (RJ45),Support bt 60W HighPower LAN(1~2):10/100/1000Mbps uplink ports (RJ45) SFP:10/100/1000Mbps SFP port
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:11.2Gbps Network Latency(10 to 1000Mbps): 16μs (usethe 64byte packagesize) MAC address table: 8K The FrameFilter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3af/at/bt Power over Ethernet

Power Support	Power Input:AC 90~240V Totals120W AI Watchdog: Port 1~8 Power Output:PoE1~6 Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 310mm*260mm*100mm, Weight:1.6KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device:1 year
Package Content	AC Power Cable,User Manual