

GNT-P4813V6

GNT-P4813V6 16p 2Up-Link 1SFP 250m AI PoE Switch Genata



Model	GNT-P4813V6
Brend	Genata
PoE gücü	300 W
Port sayı	16 Port
PoE	PoE
Port sürati	100mb/s

Specification

GNT-P4813V6	Product Features
Total 300W PowerSupply 16 ports PoE	AI Watchdog Function
2 ports Uplink	6KV Lightning & 8KV ESD Protection Support bt 60W High Power
1 port SFP	Auto-Adaption 250m Transmission
Specifications	
Ports	PoE (1~14):10/100Mbps PoE ports(RJ45) PoE (15):10/100Mbps PoE port,Support bt 60W HighPower PoE (16):10/100/1000Mbps PoE port (RJ45),Support bt 60W High Power LAN(1~2):10/100/1000Mbps uplink ports (RJ45) SFP:10/100/1000Mbps SFP port
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000 Mbps HalfDuplex
Transmission Distance	100Mbps /10Mbps, Auto-Adaption 250m
Performance Specification	Bandwidth:12.8Gbps NetworkLatency (10 to 1000Mbps): 16μs(use the 64bytepackage size) MAC address table: 8K The Frame Filter& Transmission Rate:14800pps the mostfor 10M port, 148800pps the mostfor 100M port;1488000pps the most for1000M port

Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x FlowControl IEEE 802.3af/at/bt Powerover Ethernet
Power Support	Power Input: AC 90~240V Totals 300W PoE Watchdog: Port1~16 Power Output: PoE1~14 Port: 1/2(+52V), 3/6(GND) ≤ 30W PoE15~16 Port: 1245(+53V), 3678(GND) Compatible 1/2(+52V), 3/6(GND) ≤ 60W
Protection Level	Lightning Protection: 6KV, Per: IEC61000-4-5 ESD Protection: 8KV, Per: IEC61000-4-2
Physical Specifications	Size(L*W*H): 430mm*180mm*45mm, Weight: 2.65KG
Working Environment	Operating Temperature: -30~60 Storage Temperature: -40~70 Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark FCC Part15, ClassB RoHS 2.0
Package Content	AC PowerCable, User Manual