

HAC-HDW1200EMP-A-0280B

2 meqapiksel HD-CVI səsli kamera; Piksel 1920x1080; IR işıqlandırma - 50 m; f-2,8 mm; Bucaq-99°; Audio (mikrofon);

Model	HAC-HDW1200EMP-A-0280B
Brend	Dahua
İş mühiti	Indoor
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	50 m
Qoruma	IP67
Material	Metal



Specification

Camera					
Image Sensor	2 MP CMOS				
Max. Resolution	1920 (H) × 1080 (V)				
Scanning System	Progressive				
Electronic Shutter Speed	PAL: 1/25 s~1/100000 s NTSC: 1/30 s~1/100000 s				
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)				
S/N Ratio	>65 dB				
Illumination Distance	50 m (164.04 ft)				
Illuminator On/Off Control	Auto				
Illuminator Number	1 (IR light)				
Angle Adjustment	Pan: 0°~360° Tilt: 0°~78° Rotation: 0°~360°				
Lens					
Lens Type	Fixed-focal				
Lens Mount	M12				
Focal Length	2.8 mm;3.6 mm				
Max. Aperture	F2.0				
Field of View	2.8 mm: H: 99°; V: 55°; D: 114° 3.6 mm: H: 83°; V: 48°; D: 105°				
Iris Control	Fixed				
Close Focus Distance	2.8 mm: 0.6m (1.97 ft) 3.6 mm: 0.7 m (2.30 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify

2.8 mm	45.1 m (147.97 ft)	18.1 m (59.38 ft)	9.0 m (29.53 ft)	4.5 m (14.76 ft)
3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)
Video				
Video Frame Rate		CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H		
Resolution		1080p (1920 × 1080); 960H (960 × 576/960 × 480)		
Day/Night		Auto(ICR)/Color/B/W		
BLC		BLC; HLC; DWDR		
WDR		DWDR		
White Balance		Auto; Area white balance		
Gain Control		Auto		
Noise Reduction		3D NR		
Illumination Mode		Smart IR		
Mirror		Yes		
Privacy Masking		Off/On (8 areas, rectangle)		
Certification				
Certifications		CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 16, Subpart B		
Port				
Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port		
Power				
Power Supply		12 VDC ± 30%		
Power Consumption		Max 3.2 W (12 VDC, IR on)		
Environment				
Operating Temperature		−40 °C to +60 °C (−40 °F to +140 °F)		
Operating Humidity		<95% (RH), non-condensing		
Storage Temperature		−40 °C to +60 °C (−40 °F to +140 °F)		
Storage Humidity		<95% (RH), non-condensing		
Protection		IP67		
Structure				
Casing Material		Metal		
Product Dimensions		Φ106.0 mm × 93.6 mm (Φ4.17" × 3.69")		
Net Weight		0.44 kg (0.97 lb)		
Gross Weight		0.60 kg (1.32 lb)		
Installation		Wall mount; ceiling mount; vertical pole mount		