

HAC-HDW1200MP-0280B

2 meqapiksel HD-CVI kamera; Piksel 1920x1080; IR işıqlandırma - 30 m; f-2,8 mm; Bucaq-101°.

Model	HAC-HDW1200MP-0280B
Brend	Dahua
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Plastik
İş mühiti	Indoor



Specification

Camera						
Image Sensor		1/2.7 inch CMOS				
Effective Pixels		1920(H)×1080(V), 2MP				
Scanning System		Progressive				
Electronic Shutter Speed		PAL: 1/25s~1/100000s NTSC: 1/30s~1/100000s				
S/N Ratio		>65dB				
Minimum Illumination		0.02Lux/F1.9, 30IRE, 0Lux IR on				
Fill Light Working Distance		30 m (98.4 ft)				
IR On/Off Control		Auto; manual				
IR LED Number		12				
Pan/Tilt/Rotation Range		Pan: 0°~360° Tilt: 0°~78° Rotation: 0°~360°				
Lens						
Lens Type		Fixed-focal				
Mount Type		M12				
Focal Length		2.8 mm; 3.6 mm				
Max. Aperture		F1.9				
Field of View		2.8 mm: 119° x 101° x 54° (diagonal x horizontal x vertical) 3.6 mm: 100° x 84° x 45° (diagonal x horizontal x vertical)				
Iris Type		Fixed iris				
Close Focus Distance		2.8 mm: 0.5 m (1.7 ft) 3.6 mm: 0.8 m (2.6 ft)				
DORI Distance		Lens	Detect	Observe	Recognize	Identify

2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
3.6 mm	49.7 m (163.1 ft)	19.9 m (65.3 ft)	9.9 m (32.5 ft)	5 m (16.4 ft)
Video				
Frame Rate		CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H		
Resolution		1080P (1920×1080); 720P (1280×720); 960H (960× 576/960×480)		
Day/Night		Auto switch by ICR		
BLC		BLC/HLC/DWDR		
WDR		DWDR		
White Balance		Auto; manual		
Gain Control		Auto; manual		
Noise Reduction		2D NR		
Smart IR		Yes		
Electronic Defog		Yes		
Mirror		Off/On		
Privacy Masking		Off/On (8 area, rectangle)		
Certifications				
Certifications		CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)		
Port				
Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port		
Power				
Power Supply		12V ±30% DC		
Power Consumption		Max 3.1W (12V DC, IR on)		
Environment				
Operating Temperature		-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)		
Storage Temperature		-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)		
Protection Grade		IP67		
Structure				
Casing		Metal throughout the whole casing		
Camera Dimensions		φ93.4 mm × 79.4 mm (φ3.68" × 3.13")		
Net Weight		0.27 Kg (0.60 lb)		
Gross Weight		0.34 Kg (0.75 lb)		