

HAC-HFW1200TLMP-IL-A

DAHUA HAC-HFW1200TLMP-IL-A-0280B-S6 HDCVI 2MP BUILT IN MIC KAMERA

Model	HAC-HFW1200TLMP-IL-A
Brend	Dahua
İş mühiti	Outdoor
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	40 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Mikrofon	Mic
Qoruma	IP67
Material	Metal



Specification

Camera					
Image Sensor	2 MP CMOS				
Max. Resolution	1920 (H) × 1080 (V)				
Scanning System	Progressive				
Electronic Shutter Speed	PAL: 1/25 s~1/100000 s NTSC: 1/30 s~1/100000 s				
Min. Illumination	0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)				
S/N Ratio	>65 dB				
Illumination Distance	IR: 40 m (131.23 ft) Warm light: 40 m (131.23 ft)				
Illuminator On/Off Control	Auto				
Illuminator Number	2 (Warm light);2 (IR light)				
Angle Adjustment	Pan: 0°~360° Tilt: 0°~90° Rotation: 0°~360°				
Lens					
Lens Type	Fixed-focal				
Auto Focus	No				
Lens Mount	M12				
Focal Length	2.8 mm;3.6 mm				
Max. Aperture	F2.0				
Field of View	2.8 mm: H: 102°; V: 60°; D: 129° 3.6 mm: H: 83°; V: 48°; D: 105°				
Iris Control	Fixed				
Close Focus Distance	2.8 mm: 0.5 m (1.64 ft) 3.6 mm: 0.7 m (2.30 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify

2.8 mm	41.1 m (135.83 ft)	16.5 m (42.13 ft)	8.3 m (27.23 ft)	4.1 m (13.45 ft)
3.6 mm	50.9 m (166.99 ft)	20.3 m (66.60 ft)	10.2 m (33.46 ft)	5.1 m (16.73 ft)
Video				
Video Frame Rate		CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H		
Resolution		1080p (1920 × 1080); 960H (960 × 576/960 × 480)		
Day/Night		Auto(ICR)/Color/B/W		
BLC		BLC; HLC; DWDR		
WDR		DWDR		
White Balance		Auto;Area white balance		
Gain Control		Auto		
Noise Reduction		3D NR		
Illumination Mode		Smart IR&WL; WL Mode; IR Mode		
Mirror		Yes		
Privacy Masking		Off/On (8 areas, rectangle)		
Certification				
Certifications		CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B; UL: UL62368-1 + CAN/CSA C22.2 No. 62368-1-14		
Port				
Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port		
Audio Input		1 channel		
Power				
Power Supply		12 VDC ± 30%		
Power Consumption		Max 4.1W (12 VDC, IR on)		
Environment				
Operating Temperature		−40 °C to +60 °C (−40 °F to +140 °F)		
Operating Humidity		<95% (RH), non-condensing		
Storage Temperature		−40 °C to +60 °C (−40 °F to +140 °F)		
Storage Humidity		<95% (RH), non-condensing		
Protection		IP67		
Structure				
Casing Material		Metal front cover + plastic rear barrel + metal bracket		
Product Dimensions		198.4 mm × 80.2 mm × 76.2 mm (7.81" × 3.16" × 3")		
Net Weight		0.29 kg (0.64 lb)		
Gross Weight		0.41 kg (0.90 lb)		
Installation		Wall mount; ceiling mount; vertical pole mount		