

HAC-HFW2221DP

DAHUA - HAC-HFW2221DP (3,6mm) - 2MP HDCVI KAMERA

Model	HAC-HFW2221DP
Brend	Dahua
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	80 m
Obyektiv	Sabit
Fokus	3.6mm
İşıqlandırma	İR
Material	Metal
İş mühiti	Outdoor



Specification

Image Sensor	1/2.7" CMOS
Effective Pixels	1928(H)×1088(V), 2.1MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1.3s~1/30000s NTSC: 1s~1/30000s
Minimum Illumination	0.03Lux/F2.0, 30IRE, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 80m (262feet)
IR On/Off Control	Auto /Manual
IR LEDs	2
Lens Type	Fixed lens/ Fixed iris
Mount Type	Board-in
Focal Length	3.6mm (6mm, 8mm, 12mm Optional)
Max Aperture	F2.0
Angle of View	H: 90° (59.4°/41.4°/26.5°)
Focus Control	N/A
Close Focus Distance	800mm (1800mm, 3000mm, 8400mm) 31.50" (70.87", 118.11", 330.71")

Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 87° Rotation: 0° ~ 360°
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2No.60950-1)
Audio Interface	N/A
Power Supply	12V DC ±25%
Power Consumption	Max 5.7W (12V DC,IR on)
Operating Conditions	-30°C ~ +60°C(-22°F ~ +140°F)/ Less than90% RH * Startup should be done at above-30°C (-22°F)
Storage Conditions	-30°C ~ +60°C (-22°F~ +140°F) / Less than90% RH
Ingress Protection & Vandal Resistance	IP67
Casing	Aluminium
Dimensions	241.8mm×90.4mm×90.4mm (9.52"×3.56"×3.56")
Net Weight	0.64kg (1.41lb)
Gross Weight	0.77kg (1.69lb)
Resolution	1080P (1920×1080)