

HAC-T1A11P-0280B



Model	HAC-T1A11P-0280B
Brend	Dahua
Material	Plastik
İş mühiti	Indoor
Növ	Analoq
Meqapixel	1 MP
İşıqlandırma məsafəsi	20 m
Fokus	2.8mm
Obyektiv	Sabit
İşıqlandırma	İR

Specification

Camera					
Pixel	1 MP				
Image Sensor	1/2.7" CMOS				
Max. Resolution	1280(H)×720(V), 1MP				
Scanning System	Progressive				
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s				
Min. Illumination	0.04Lux/F2.4, 30IRE, 0Lux IR on				
S/N Ratio	>65 dB				
Illumination Distance	20 m (65.62 ft)				
Illuminator On/Off Control	Auto/Manual				
Illuminator Number	IR light				
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°				
Lens					
Lens Type	Fixed-focal				
Lens Mount	Board-in				
Focal Length	2.8mm(3.6mm optional)				
Max. Aperture	F2.4				
Field of View	H: 93°(57.6°) V: 48°(32°)				
Iris Control	Fixed				
Close Focus Distance	800mm 31.50"				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)

3.6 mm	51m(167ft)	20m(66ft)	10m(33ft)	5m(17ft)
Video				
Video Frame Rate		25/30fps@720P		
Resolution		720P (1280×720)		
Day/Night		Auto (ICR)/Color/B/W		
BLC		BLC; HLC; DWDR		
WDR		DWDR		
White Balance		Auto / Manual		
Gain Control		Auto/Manual		
Noise Reduction		2D NR		
Smart Illumination		Auto / Manual		
Mirror		Yes		
Privacy Masking		Off/On (8 areas, rectangle)		
Certification				
Certifications		CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)		
Port				
Video Output		1-channel BNC high definition video output / CVBS video output (Can switch)		
Power				
Power Supply		12 VDC ± 30%		
Power Consumption		Max. 2.3 W (12 VDC, IR on)		
Environment				
Operating Temperature		-40 °C to +60 °C (-40 °F to 140 °F)		
Operating Humidity		<95% (RH), non-condensing		
Storage Temperature		-40 °C to +60 °C (-40 °F to +140 °F)		
Protection		NA		
Structure				
Casing		Plastic		
Product Dimensions		85mm×85mm×69mm(3.35"×3.35"×2.72")		
Packaging Dimensions		164 mm × 79 mm × 90 mm (6.46" × 3.11" × 3.54")		
Net Weight		0.09kg (0.20lb)		
Gross Weight		0.13kg (0.27lb)		
Installation		Wall mount; ceiling mount; horizontal pole mount		