

MS105GP

MERCUSYS MS105GP UN 5-Port Gigabit Desktop Switch with 4-Port PoE+



Model	MS105GP
Brend	Mercusys
Port sayı	5 Port
PoE	PoE+
PoE gücü	60 W
Port sürati	100mb/s

Specification

Category	Details
Hardware Standards and Protocols	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, CSMA/CD
Dimensions	99.8 × 98 × 25 mm
PoE Ports	RJ45 Standard: Compliant with 802.3 af/at Powered Devices PoE Ports: Port 1 - Port 4 PoE Power Budget: 65 W
Interfaces	5× 10/100/1000 Mbps Ports, Auto-Negotiation, Auto MDI/MDIX
External Power Supply	External Power Adapter (Output: 53.5V/1.31A)
Installation	Desktop Wall Mount
Data Rates	10/100/1000 Mbps at Half Duplex 20/200/2000 Mbps at Full Duplex
Jumbo Frame	9 KB
LED Indicators	Ethernet Ports (1–5), Power
MAC Address Table	2K
Max Power Consumption	3.13W (220 V / 50 Hz, no PD connected) 75.15W (220 V / 50 Hz, with 65W PD connected)
Max Heat Dissipation	10.64 BTH/h (no PD connected) 255.51 BTH/h (with 65W PD connected)
Software – Transfer Method	Store and Forward
Management	Plug and Play

Category	Details
Advanced Features	802.3x Flow Control IGMP Snooping V1/V2/V3 Isolation Mode Extend Mode
Package Contents	• 5-Port Gigabit Desktop Switch with 4-Port PoE+ (MS105GP) • Power Adapter • Quick Installation Guide
Environment	Operating Temp: 0~40 (32~104) Storage Temp: -40~70 (-40~158) Operating Humidity: 10%~90% RH Storage Humidity: 5%~95% RH