

NSW2020-24T1GT1GC-POE-IN

NSW2020-24T1GT1GC-POE-IN 24 Port PoE Network Switch With GB Uplink UNV



Model	NSW2020-24T1GT1GC-POE-IN
Brend	Uniview
Port sayı	24 Port
PoE	PoE
PoE gücü	400 W
Port sürati	100mb/s

Specification

Model	NSW2020-24T1GT1GC-POE-IN
Ports	24×100Mbps PoE ports (RJ45) + 1×1000Mbps Gigaethernet ports +1×1000Mbps Combo ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab, IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az
Switching capacity	8.8Gbps
Forwarding performance	6.55Mpps
Packet Buffer	4Mbit
MAC	16K
Dimensions (W×D×H)	440*250*44mm
Weight	2.93KG
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af 4/5+7/8-
Max. PoE Power	Max capacity: 370W Max capacity for single port: 30W
Prior Ports	1~8
Cooling Fans	1
Operating temperature	0°C-40°C (32°F-104°F)
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	POWER: Steady on: AC input is normal Off: No AC input

PoE:
Off: No PoE power supply
Steady on: PoE power supply is normal

PoE-MAX:
off :The POE power supply power of the whole machine is less than 80% of the specification
Steady on : The POE power supply power of the whole machine is greater than 85% of the specification

LINK/ACT:
Off: No link
Steady on: Linked
Flashing:
Transmitting data

Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. Enabling PD keepalive function, the switch will restart the IPC via PoE power when the IPC sends no message in a period of time. Extend(Surveillance mode): Transmission distance up to 250 meters. Downlink ports can communicate only with uplink ports.
--------------	--