

OC200(UN)

TP -LINK OMADA CLOUD CONTROLLER OC200(UN)

Model	OC200(UN)
Brend	Tp-Link
Tip	Cloud Controller
Port sürəti	100 mb/s



Specification

HARDWARE FEATURES	
Interface	• 2× 10/100 Mbps Ethernet Port • 1× USB 2.0 Port • 1× Micro USB Port
Power Supply	802.3af/at PoE or Micro USBⓂDC 5V/Minimum 1AⓂ
Dimensions	3.9×3.9×1.0 in (100×98×25 mm)

MANAGEMENT	
Omada App	Yes
Centralized Management	• Up to 100 Omada access points, 20 JetStream switches, and 10 Omada routers • Up to 1,000 Clients Note: Please refer to www.tp-link.com/en/business-networking/all-omada/ to find all the device models supported by OC200
Cloud Access	Yes
L3 Management	Yes
Multi-site Management	Yes
Management Features	• Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule • Captive Portal Configuration

OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• Omada Hardware Controller OC200 • Quick Installation Guide • Ethernet Cable
System Requirements	Microsoft® Windows®10, 8, 7,Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux

OTHERS	
Environment	• Operating Temperature: 0~40 ℃ (32~104 ℉) • Storage Temperature: -40~70 ℃ (-40~158 ℉) • Operating Humidity: 10~90% RH non-condensing • Storage Humidity: 5~90% RH non-condensing