

PFS3008-8GT-60

Dahua PFS3008-8GT-60 8 Port Full Gigabit PoE Switch; PoE - 60W



Model	PFS3008-8GT-60
Brend	Dahua
Port sayı	8 Port
Port sürati	1000mb/s
PoE	PoE
PoE gücü	60 W

Specification

Hardware	
Data Transmission Port	Port 1-4: 4 × RJ-4510/100/1000 Mbps (PoE) Port 5-8: 4 × RJ-45 10/100/1000 Mbps
Power Supply	48 V-57 V DC
Operaing Temperature	-10 °C to + 55 °C(+14 °F to + 131 °F)
Operating Humidity	5%~95% (RH)
Storage Temperature	-20 °C to + 70°C (-4 °F to + 158°F)
Storage Humidity	5%~95% (RH)
Power Consumption	Idling: 3.0 W Full load: 60 W
Performance	
Capacity	20 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mbit
MAC Table Size	8K
Communication Standard	IEEE802.3; IEEE802.3u; IEEE 802.3ab; IEEE802.3X
PoE	
PoE Standard	IEEE802.3af; IEEE802.3at; Hi-PoE
PoE Power	60 W
Power Consumption Management	Yes
PoE Pin Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
Long Distance PoE	Supports 250 m (820.21 ft)
General	
Statics Protection	Air discharge: 8 kV Contact discharge: 6 kV
Thunder-proof	Common mode: 2 kV Differential mode: 0.5 kV
Net Weight	490 g (1.08 lb)

Product Dimensions	190 mm × 100 mm × 30 mm (7.48" × 3.93" × 1.18") (W × L × H)
--------------------	---

Transmission Performance:		
Switch power supply voltage 53V.		
CAT5E/CAT6. Max. DC resistance < 10 ?/100 m		
Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
IEEE802.3bt 90 W		
100	71.3	100
150	62	10
200	51	10
250	40	10
Hi-PoE 60 W		
100	53	100
150	50	10
200	47	10
250	37	10
IEEE802.3at 30 W		
100	25.5	100
150	25.5	10
200	25.5	10
250	25.5	10
Note: Data from this table was collected by Dahua test lab and is for reference only . The actual transmission distance may vary due to power consumption of connected devices or the cable type and status.		