

TAPO C410 KiT

TP-LINK TAPO C410 KiT SOLAR-POWERED (Rechargeable Lithium-ion Battery) SECURITY WI-FI CAMERA

Model	TAPO C410 KiT
Brend	Tp-Link
Meqapixel	3 MP
Səs	İkitərəfli səs
Enerji mənbəyi	Batareya
Gecə görmə məsafəsi	10m
Micro SD	512Gb
Internet	Wifi



Specification

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS Starlight Sensor
Lens	Focal Length: 3.17 mm Aperture: F1.65 Field of View: 125° (Diagonal), 111°(Horizontal), 56°(Vertical)
Night Vision	850 nm IR LED (30 ft / 9.1 m) Full-Color Night Vision
Lighting	2× Spotlights
Interface & Button	1× POWER Button 1× RESET Button 1× MicroSD Card Slot (Up to 512GB)
SOLAR PANEL	
Connection Capacity	A solar panel can only connect to one camera.
Output Port	Type-C
VIDEO & AUDIO	
Maximum Resolution	2K 3MP (2304 × 1296 px)
Frame Rate	15 fps
Video Compression	H.264
Live View	Yes
Image Enhancement	3D DNR WDR
Audio Input & Output	Built-in Microphone and Speaker

	CAMERA
Audio Communication	Two-Way Audio with Noise Cancellation
Siren Volume	94 dB (Level measured at 4-inch/10-cm distance)
STORAGE	
Local Storage	MicroSD Card Slot on Camera (Up to 512 GB)
Cloud Storage	Tapo Care Cloud Storage Services (Subscription required)
DETECTION and NOTIFICATIONS	
Sensor	Single Motion Sensor (FOV: 110° horizontal) Single Ambient Light Sensors
AI Detection	Motion Detection Person Detection
Activity Zones	Yes
Output Notification	System Notification System Notification with Snapshot (Tapo Care Services)
NETWORK	
Network Connectivity	Connect via Wi-Fi
Wireless Connectivity	IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
SECURITY	
Security	128-bit AES Encryption with SSL/TLS WPA/WPA2-PSK
POWER	
Power Source	Built-in Rechargeable Lithium-ion Battery Solar Panel: Tapo A201
Input Voltage	Adapter Input: 100-240 V, 50/60 Hz
Output Voltage	Adapter Output: 5.0 V, 1.0 A Solar Panel Max Charging Voltage: 5.2 V Solar Panel Max Charging Power: 2.5 W
GENERAL	
Smart Integration	Google Assistant, Amazon Alexa
Weather Resistance	IP65
System Requirements	Tapo App: iOS 11.0 or higher, Andriod 5.0 or higher
Mounting Options	Tabletop Ceiling-Mounted Wall-Mounted
Operating Temperature	-20℉~45℉
Storage Temperature	-20℉~60℉
Operating Humidity	10%~90% RH, Non-condensing
Storage Humidity	5%~90% RH, Non-condensing
Charging Temperature	0-45℉
Dimensions (W x D x H)	Camera Dimensions: D60mm × 89mm Solar Panel Dimensions: 173.42 × 120.42 × 15.7 mm (6.83 × 4.74 × 0.62 in)
Package Content	Tapo C410 Camera ×1 Tapo A201 Solar Panel ×1 Tapo A201 Solar Panel Bracket ×1 USB Adapter Cable ×1 Base Cover ×1 Extension Wire ×1 Mounting Screws ×6 Mounting Anchors ×6 Waterproof Seals ×2 Screw Caps ×2 Cable Zip Tie ×1 Mounting Templates ×2 Quick Start Guide
Certifications	CE, FCC, DOE, CEC, RCM, KC, NCC, BSMI, NTRA, IP65