

TL-LS1210GP

TP -LINK TL-LS1210GP (UN) 10-PORT GIGABIT DESKTOP SWITCH WITH 8-PORT POE+



Model	TL-LS1210GP
Brend	Tp-Link
PoE gücü	60 W
Port sayı	8 Port
PoE	PoE
Port sürati	1000mb/s

Specification

HARDWARE FEATURES	
Interface	• 9× 10/100/1000 Mbps RJ45 Ports (Ports 1–8 supports PoE+ output) • 1× Gigabit SFP Port
Network Media	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Installation	• Desktop • Wall Mounting
Physical Security Lock	Yes
Power Supply	External Power Adapter(Output: 53.5VDC / 1.31A)
PoE+ Ports(RJ45)	• Standard: 802.3at/802.3af compliant • PoE Ports: Ports 1–8, up to 30 W PoE output per port • PoE Power Budget: 61W
Dimensions (W x D x H)	8.2×4.9×1.0 in (209×126×26 mm)
Max Power Consumption	• 7.3 W (220/50Hz. no PD connected) • 76.96 W (220/50Hz. with 61 W PD connected)
Max Heat Dissipation	• 24.82 BTU/h (no PD connected) • 261.66 BTU/h (with 61 W PD connected)
PERFORMANCE	
Switching Capacity	20 Gbps
Packet Forwarding Rate	14.88 Mpps
MAC Address Table	4K
Jumbo Frame	16 KB

HARDWARE FEATURES	
SOFTWARE FEATURES	
Advanced Features	• Extend Mode Button (Ports 1–4, Up to 250 m PoE power supply and data transmission) • Isolation Mode Button (Ports 1–8) • PoE Auto Recovery Button (Ports 1–8) • Compatible With IEEE 802.3af/at Compliant PDs • IEEE802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping • Green Technology
Transmission Method	Store-And-Forward
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• LS1210GP • Power Adapter • Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing