

# UAC-B112-AF28

HDTVI CAM UNV UAC-B112-AF28 ( 2MP , Built-in Mic )

|                       |               |
|-----------------------|---------------|
| Model                 | UAC-B112-AF28 |
| Brend                 | Uniview       |
| İş mühiti             | Outdoor       |
| Növ                   | Analoq        |
| Megapixel             | 2 MP          |
| Mikrofon              | Mic           |
| İşıqlandırma          | İR            |
| İşıqlandırma məsafəsi | 20 m          |
| Obyektiv              | Sabit         |
| Fokus                 | 2.8mm         |
| Qoruma                | IP67          |
| Material              | Plastik       |



## Specification

|                       |                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------|
| Model                 | UAC-B112-AF28                                                                              |
| Sensor                |                                                                                            |
| Pixel                 | 2MP                                                                                        |
| Size                  | 1/3"                                                                                       |
| Minimum illumination  | 0.02 lux (F2.0, AGC ON)<br>0 lux (IR ON)                                                   |
| Lens                  |                                                                                            |
| Lens                  | 2.8mm                                                                                      |
| Lens mount            | M12                                                                                        |
| Angle of view         | H: 90.5° V: 49.6° D: 109.5°                                                                |
| Illuminator           |                                                                                            |
| Illuminator           | One IR illuminator                                                                         |
| Illumination distance | 20m                                                                                        |
| Lifetime              | ≥60,000 hours                                                                              |
| Video                 |                                                                                            |
| Resolution            | 1080P: 1920(H)×1080(V)<br>720P: 1280(H) ×720(V)                                            |
| Frame rate            | TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps<br>CVBS: PAL, NTSC |
| Shutter time          | PAL: 1/25s-1/50000s<br>NTSC: 1/30s-1/50000s                                                |
| Image                 |                                                                                            |
| Exposure mode         | Four modes: Global (default), BLC, HLC, DWDR                                               |

|                         |                                                                                                                                          |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Day/Night               | Three modes: Auto (default), Day, Night                                                                                                  |
| Digital noise reduction | 2D/3D                                                                                                                                    |
| White balance           | Two modes: Auto (default), Manual                                                                                                        |
| WDR                     | DWDR                                                                                                                                     |
| Smart IR                | Support                                                                                                                                  |
| Flip                    | Supports 180° horizontal flip, 180° vertical flip                                                                                        |
| Defog                   | N/A                                                                                                                                      |
| Audio                   |                                                                                                                                          |
| Microphone              | Built-in Mic                                                                                                                             |
| Camera audio            | TVI: 1080P@25fps, 1080P@30fps<br>CVI: 1080P@25fps, 1080P@30fps                                                                           |
| Interface               |                                                                                                                                          |
| Power                   | 5.5mm power interface                                                                                                                    |
| Video output            | BNC, supports TVI/AHD/CVI/CVBS                                                                                                           |
| Operating environment   |                                                                                                                                          |
| Temperature             | -30°C to 60°C (-22°F to 140°F)                                                                                                           |
| Humidity                | ≤95% (RH, non-condensing)                                                                                                                |
| Surge protection        | 4kV                                                                                                                                      |
| General                 |                                                                                                                                          |
| Power                   | DC 12V (±25%), with reverse polarity protection, Max 2.2W                                                                                |
| Mount                   | Surface mount (default), optional backbox, pole mount bracket                                                                            |
| Dimensions              | 142mm*63mm*65mm (L*W*H)                                                                                                                  |
| Material                | Plastic                                                                                                                                  |
| Weight                  | 135g(0.30lb)                                                                                                                             |
| OSD menu language       | 11 Languages<br>English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish |
| Certification           |                                                                                                                                          |
| EMC                     | CE-EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035)<br>FCC (FCC 47 CFR part15 B)                                                    |
| Safety                  | CE-LVD (EN 62368-1)                                                                                                                      |
| Environment             | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)                                                                                     |
| Protection              | IP67 (IEC 60529)                                                                                                                         |