

UAC-B112-AF28-W

HDTVI CAM UNV UAC-B112-AF28-W (2MP ColourHunter)

Model	UAC-B112-AF28-W
Brend	Uniview
İş mühiti	Outdoor
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	20 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik



Specification

Model	UAC-B112-AF28-W
Sensor	
Pixel	2MP
Size	1/3"
Minimum illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	
Lens	2.8mm
Lens mount	M12
Angle of view	H: 100.9° V: 56.5° D: 121.8°
Illuminator	
Illuminator	One white-light illuminator
Illumination distance	20m
Lifetime	≥60,000 hours
Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame rate	TVI/AHD/CVI: 1080P@25fps (default), 1080P@30fps, 720P@25fps, 720P@30fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Image	
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR

Day/Night	24/7 color images
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	Supports 180° horizontal flip, 180° vertical flip
Defog	N/A
Audio	
Microphone	Built-in Mic
Camera audio	TVI: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
Operating environment	
Temperature	-30 to 60 (-22 to 140)
Humidity	≤95% (RH, non-condensing)
Surge protection	4KV
General	
Power	DC 12V(±25%), with reverse polarity protection, Max 2.3W
Mount	Surface mount (default), optional backbox, pole mount bracket
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Graphene+Plastic
Weight	146g(0.32lb)
OSD menu language	11 Languages English, German, Spanish(Latin America), French, Italian, Japanese, Korean, Polish, Portuguese(Brazil), Russian, Turkish
Certification	
EMC	CE-EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE-LVD (EN 62368-1)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU)
Protection	IP67 (IEC 60529)