

USW-LITE-8-POE

UBIQUITI UNIFI SWITCH LITE 8 (USW-LITE-8-POE) An 8-port, Layer 2 PoE switch supporting silent fanless cooling. (4) GbE PoE+, (4) GbE ports, 52W total PoE availability*, Wall mountable, *With an external 60W power adapter.



Model	USW-LITE-8-POE
Brend	Ubiquiti
Port sayı	8 Port
Tip	Smart
PoE	PoE
Port sürəti	1000mb/s
PoE gücü	60 W

Specification

Dimensions	99.6 x 163.7 x 31.7 mm (4 x 6.4 x 1.3")
Weight	295 g (10.4 oz)
Enclosure material	Polycarbonate
Management interface	Ethernet In-Band
Networking interface	(8) GbE RJ45 ports
PoE interface	(4) PoE/PoE+ (Pins 1, 2+; 3, 6-)
Total non-blocking throughput	8 Gbps
Switching capacity	16 Gbps
Forwarding rate	11.904 Mpps
Power method	54V DC, 1.1A power adapter
Power supply	54V, external, 60W
Supported voltage range	50–57V DC
Max. power consumption	8W (Excluding PoE output)
Total available PoE	52W* *With an external 60W power adapter.
Max. PoE wattage per port by PSE	PoE+: 30W
Button	Factory reset
Ambient operating temperature	-15 to 40° C (5 to 104° F)
Ambient operating humidity	10 to 90% noncondensing

Certifications	CE, FCC, IC
Layer 2 features	IGMP snooping STP / RSTP with priorities and port-level disable Port isolation Storm control Voice VLAN Port mirroring LACP port aggregation Multicast / broadcast rate limiting MAC address blocking Flow control 802.1X control Jumbo frames Proprietary loop protection DHCP snooping / guarding Egress rate limit LLDP-MED Port restricted by MAC Device isolation with ACLs
Layer 3 features	-
System	Status
Ethernet	PoE Speed/link/activity
PoE	Link/activity
UniFi Network	Version 7.2.94 and later