

VIGI NVR2016H-16MP

TP-LINK VIGI NVR2016H-16MP UN 16 CHANNEL POE+ NETWORK VIDEO RECORDER, 16 kanal PoE+ dəstəyi ilə təchiz olunmuş şəbəkə video qeydiyyatçısıdır. Bu cihaz, 4K HDMI və VGA çıxışları ilə yüksək keyfiyyətli görüntü təqdim edir və H.265+ sıxışdırma texnologiyası sayəsində yaddaş və bant genişliyinə qənaət edir. 32TB-a qədər SATA HDD dəstəyi ilə uzunmüddətli video saxlama imkanı verir. ONVIF protokolu ilə müxtəlif markalı IP kameralarla uyğun işləyir. VIGI tətbiqi və veb interfeysi vasitəsilə uzaqdan izləmə və idarəetmə mümkündür.



Model	VIGI NVR2016H-16MP
Brend	Tp-Link
Növ	NVR
Kanal sayı	16 kanal
PoE dəstəyi	PoE
Məqəpəxel	8 MP
Max HDD sayı	2 HDD
Max HDD həcmi	16 TB

Specification

Video and Audio	
IP Video Input	16-Channel
Incoming Bandwidth	320 Mbps
Outgoing Bandwidth	320 Mbps
HDMI Output Resolution	1 Channel, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
VGA Output Resolution	1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz
Video Output Mode	HDMI and VGA Independent / Simultaneous Output
Multi-View Display	1/4/6/8/9/16
DECODING	
Audio Compression	G.711A/G.711U/G.726
Video Compression	H.265+/H.265/H.264+/H.264
Record Resolution	8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-Channelt

Video and Audio	
Capability	• 25fps: 10-ch @ 3MP, 16-ch @ 1080P • 30fps: 4-ch @ 8MP, 6-ch @ 5MP, 8-ch @ 4MP
Record Management	
Record Mode	• Manual Recording • Scheduling Recording • Motion Detection Recording
Playback Mode	• Instant Playback • Regular Playback • Tag Playback • Event Playback
Backup Mode	• Regular Backup • Video Clip Backup
Playback Function	• Play • Pause • Stop • Fast Forward • Fast Backward • Play By Frame • Full Screen • Video Clip • Export Clip • Digital Zoom • Lock Recording • Audio On/Off
NETWORK	
Protocol	UPnP (Plug and Play), NTP (Network Timing), SMTP, DNS, TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, RTSP, SSL/TLS, RTP, IPv4, ARP, FTP/SFTP, IPv6, SNMP
Mobile Phone Access	Android, iOS
Web Browser	Chrome (57+), Firefox (52+), Edge (91+), Safari (11+)
Interoperability	ONVIF Profile S, CGI
External Interface	
Network Interface	1, RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
USB Interface	1 Front USB 2.0 Port, 1 Rear USB 3.0 Port
Audio Interface	1-ch RCA Input; 1-ch RCA Output
Alarm In/Out	6/4
Serial Interface	N/A
Power	1× DC Jack
Reset Button	1
Speaker	N/A
eSATA	1*
HDMI	1
VGA	1
HARD DISK	
SATA	2 SATA Interfaces
Capacity	Up to 16 TB Capacity for Each HDD*
PoE	
Standard	802.3at/af Compliant
Interface	1-16, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface
PoE Budget	140W Available for All PoE+ Ports, 30 W Max per Port
Alarm	

Video and Audio	
General Alarm	• Motion Detection • Video Tampering • Scene Change Detection • Line-Crossing Detection • Intrusion Detection • Region Entering Detection • Region Exiting Detection • Loitering Detection • Object Abandoned/Removal Detection • Vehicle Detection • Human Detection • Abnormal Sound Detection • Smart Frame Note: The alarm function requires the use of a camera.
Anomaly Alarm	• Video Loss • Offline and IP Conflict • Disk Exception • Login Exception • Fan Exception
Alarm Linkage	• Recording • White Light Alarm • Buzzer • Log • Audible Alarm Note: The alarm function requires the use of a camera.
GENERAL	
Storage Temperature	-40 ℃ to 70 ℃ (-40 ℉ to 158 ℉)
Storage Humidity	10%~90% RH Non-Condensing
Package Content	• VIGI Network Video Recorder • Power Adapter • Terminal Blocks • HDD Power Cables • HDD Data Cables • Mounting Brackets • Screws • Rubber Feet • Mouse • Quick Installation Guide
Working Temperature	• NVR: -10 ℃ to 55 ℃ (14 ℉ to 131 ℉) • Power Adapter: 0 ℃ to 40 ℃ (32 ℉ to 104 ℉)
Working Humidity	10%~90% RH Non-Condensing
Dimensions(W X D X H)	13.0 × 11.2 × 1.8 in (330 × 285 × 45 mm)
Net Weight	2.2 Kg#
Gross Weight	4.2 Kg#
Power Supply	53.5V DC/3.37A
Max. Power Consumption	• 6.2 W (Without Disk) • 40 W (With Disk)
Certifications	CE, NTRA, BSMI, VCCI, FCC, HDMI, ONVIF