XP-80K

XPRINTER RECEIPT XP-80K USB+LAN

Model	XP-80K
Brend	Xprinter
Növ	Printer
Printerin tipi	Çek
Printer qoşulma	USB+LAN

Specification

Printing		
Printing method	Direct thermal	
Media width	79.5±0.5mm / φ 80 mm	
Print width	72mm	
Column capacity	576 dots/line or 512 dots/line	
Printing speed	230mm/s	260mm/s
Interface	USB / USB+Serial / USB+Lan / (Optional: Bluetooth/Wifi)	USB+Serial+Lan (Optional: Bluetooth/Wifi)
Line spacing	3.75mm (Adjustable by commands)	
Character size	ANK：Font A：1.5×3.0mm（12×24 dots） Font B：1.1×2.1mm（9×17 dots） Chinese,traditional Chinese:3.0×3.0mm（24×24 dots）	
Barcode Character		
Extension character sheet	PC437（Standard Europe）、Katakana：PC850（Multilingual）、PC860（Portuguese）、PC863（Canadian-French）、PC865（Nordic）、West Europe：Greek：Hebrew：East Europe：Iran：WPC1252：PC866（Cyrillic#2）、PC852（Latin2）、PC858（IranII）、Latvian：Arabic：PT151：1251：	
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	96 Kbytes: USB+Serial / USB 256 Kbytes: USB+Lan	256 Kbytes
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100V/240V, 50～60Hz; Output：DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	0.89 KG	
Dimensions	168 × 130 × 123.5mm(D×W×H)	
Environmental Requirements		
Work environment	Temperature(0～45℃) humidity(10～80%)	
Storage environment	Temperature(-10～60℃) humidity(10～90%)	

Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC / POS
Driver	Windows / Linux / Mac OS / Android